ESS-261KLC-SA1

Energy storage cabinet



Efficient & Flexible

- PCS supports both on-grid and off-grid applications
- Multiple cabinets can be connected in parallel to support large capacity application

Safety & Friendly

- Battery uses liquid cooling and PTC heating, adaptable to various harsh environments
- Noise level less than 70dB(A), enviromental friendly
- Intrinsic & Active & Passive ultimate safety design

Smart management

- Built-in EMS, supports demand management, PV fusion, micro grid, etc.

www.sofarsolar.com

© As of December 2025, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

Model	ESS-261KLC-SA1
DC Side	
Battery Type	LFP/314Ah
Series and Parallel Mode	1P260S
Rated Energy	261 kWh
Nominal Voltage	832V
DC Operating Voltage Range	650V~949V
Depth of Discharge (DOD)	98%
AC Side	
Type	3P4W
AC Voltage	400V AC
Rated AC Power	125 kW
Maximum AC Power	138 kW
Rated Grid Frequency	50Hz/60Hz
Power Factor	-1~1
Unbalanced Load	0~100%
System Parameters	
Cycle Performance	≥8000 @ 70% SOH
Round Trip Efficiency (RTE)	88%@0.5P, 90%@0.25P
Operating Ambient Temperature	-30˚C~50˚C (derating above 45˚C)
Storage Ambient Temperature	-30˚C~60˚C
Operating Relative Humidity	0~100% (No Condensation)
Operating Altitude	≤ 4000m
Ingress Protection Rating	IP55
Anti-Corrosion	C4-M (C5-M Optional)
Cooling Type	Liquid Cooling
Fire Detection	Smoke, Temperature, CO
Fire Suppression	Three Level Fire Suppression Cell & Pack Space Level: Perfluorohexanone Spray (Optional) Baterry Room Level: Aerosol/Perfluorohexanone Spray (Optional) Whole Cabinet Level: Water Spray
Explosion Protection	Two Level Explosion Suppression Directional Smoke Extraction Explosion Venting Panel
Installation	Ground Mounting
Communication	Modbus TCP
Dimension (W×D×H)	1000×1350×2500mm
Weight	< 2400kg
Noise	≤ 70dB(A)
Standard	IEC62619, IEC62477-1, IEC/EN 61000-6-2/4, EN50549-1, UN38.3, UN3480

*All specifications are subject to change without notice.